











All the technical information given in this document is correct to the best of our knowledge and based on our experience, but assumes no legal responsibilities and cannot accept any claim for consequential liability.

- No flowing under pressure and temperature.
- > Reliable sealing of gases and liquids.
- Excellent resistance to thermal fluctuations.
- Health and environment friendly.
- > Unlimited shelf life.
- > Very little swelling in oil and fuels.
- Low permeability to gas with little surface pressure.
- Favourable price to performance ratio.

## **Technical Data**

Temperature Short term service temperature 350°C

Continuous service temperature 300°C

Chemical Resistance PH 2 - 14

Tensile Strength

Compressibility

Recovery

ASTM F 152 / 8N mm<sup>2</sup>

ASTM F 36 7% to 17%

ASTM F 36 50%

## **Applications**

Hydrocarbons, Solvents, Alcohols glycols, Aqueous solutions, Water, Steam, Alkaline solutions and Organic acids. (Not recommended for hydro fluoric acid and concertrated nitric acid.)

## **Sheet Size**

1.5 Mtrs. X 2 Mtrs.

Thickness: 0.5 mm/1mm/1.5mm/2mm/3mm/4mm/5mm



ISO 9001 : 2000 REGISTERED COMPANY

231, 5/B Mittal Industrial Estate, Marol, Andheri (E), Mumbai - 400 059, India. 91-22-28501805 • Fax : 91-22-2850 0314

E-mail: masseal@vsnl.com Website: www.masseal.com

